

CITY OF HERITAGE CREEK

**ADVERTISEMENT FOR BIDS
STREET CRACK FILLING AND SEAL COATING**

The City of Heritage Creek, Jefferson County, Kentucky, will received sealed bids for filling asphalt cracks as needed and for seal coating the following streets within the City of Heritage Creek:

Temperate Court; Justice Way; Persistence Drive; Destiny Cove; Reality Trail; Courage Court; Wisdom Lane; Vision Place; United Blvd.; Tenacity Court

Sealed bids will be received until 2 p.m. on September 12, 2025 at the City of Heritage Creek, City Hall, Clerk's Office, 8700 Justice Way, Louisville, Jefferson County, Kentucky 40229 and be clearly marked on the outside "Sealed Bid for the City of Heritage Creek Street Repair". The bids will be opened at 12 p.m. on September 15 2025 and read aloud at that time.

The City of Heritage Creek reserves the right to reject any and all bids.

Bid Documents are available at the City of Heritage Creek, 8700 Justice Way, Louisville, Kentucky 40229 between the hours of 8am and 2pm on Monday, Tuesday, Thursday, days of the week until September 11 Friday.

INSTRUCTIONS TO BIDDERS

Bids will be received by the City Clerk of the City of Heritage Creek, Kentucky, at the place and time specified in the Advertisement for Bids. The bids will be publicly read aloud for the information of bidders and others properly interested who may be present either in person or by representative at the place and time specified in the Advertisement for Bids.

PREPARATION OF BIDS

A. Bids shall be submitted in strict compliance with the requirements of the Advertisement for Bids. All bid prices shall be fully and clearly set forth.

B. Each bid must give the full address of an individual bidder and be signed. Bids by a partnership must furnish the full names of all partners and must be signed with the partnership name by one of the members of the partnership or by an authorized representative, followed by the signature and title of the person signing. Bids by corporations must be signed with the legal name of the corporation, and by the signature and title of the president, secretary or other person authorized to bind it in the matter. The name of the person signing shall also be typed or printed below the signatures.

C. Erasures or other changes in the bids must be explained or noted over the signature of the bidder.

D. The bid shall also include a resume of the bidder.

TIME OF OPENING OF BIDS

Bids received prior to the time of opening will be kept unopened in a secure place. The officer whose duty it is to open them will decide when the specified time has arrived, and no bid received thereafter will be considered. No responsibility will attach to an officer for the premature opening of a bid not properly addressed and identified.

AWARD OF CONTRACT

The right is reserved to reject any and all bids. The City Council of Heritage Creek, Kentucky, may determine, in its sole discretion conformity with the published Advertisement for Bids.

SPECIFICATIONS

A. Conform to all requirements of the Kentucky Transportation Cabinet/Department of Highways 2019 Standard Specifications for Road and Bridge Construction.

B. Apply In-Place Asphalt Hot Pour Crack Sealant as needed and Asphalt Based Pavement Sealer.

- Crack Filling – The crack must be free from moisture, dust, and loose aggregate. Routing or wire brushing are preferred methods followed by a compressed air heat lance immediately prior to sealing. The substrate and air temperature must be above 40°F.
- Seal Coat – Equipment. Provide, and keep on the project at all times, an accurate thermometer, hand brooms, and other small tools and equipment essential for completion of the work.

Provide equipment for heating the asphalt material and pressure distributors.

Provide a mechanical broom or sweeper for cleaning the existing surface.

Weather Limitations. Do not construct any seal coat when the ambient temperature is below 45°F nor when the ambient temperature within the preceding 24 hours has been 35°F or lower.

Preparation of Surface. Sweep the road with a mechanical sweeper and with wire hand brooms, when necessary. Clean the edges of the surface so that the full width of the roadway to be treated is uniformly clean. Where any mud or earth exists, remove it in advance of the application of the asphalt material. And allow the surface to thoroughly dry.

Heating and Applying Asphalt Materials. Heat and maintain the asphalt material between 125 and 175°F during application.

Apply asphalt material by means of a pressure distributor in a uniform, continuous spread over the section to be treated.

Keep the nozzles of the spray bar clear at all times. Immediately make any streaked areas uniform by use of a hand hose equipped with a nozzle.

Treat areas over which it is impractical to operate a distributor by means of a hand hose equipped with a nozzle or by means of a pouring pot.

When the seal coat treatment is constructed in half-widths, provide complete coverage by overlapping the 2 applications approximately 4 inches along the centerline.

Prevent spotting or discoloring curbs, headwalls, and other structures.

Make joints utilizing an approved method.

- Sealer shall be applied by mechanical squeegee/brush equipment or spray equipment capable of spraying coatings with sand. Equipment shall have continuous agitation or mixing capabilities to maintain homogenous consistency of mixed material throughout the application process. Truck mount or self-propelled squeegee/brush equipment shall have at least 2 squeegee or brush devices (one behind the other) to assure adequate distribution and penetration of mixed Sealer into bituminous pavement. Hand squeegees and brushes shall be acceptable in areas where practicality prohibits the use of mechanized equipment.
- All bidders must carry a warranty for work performed in this bid for one calendar year from the last day of performing said work.
- Provide Traffic Control during project.